

(11) (A) No. 1088024

(45) ISSUED 801021

(52) CLASS 204-103  
C.R. CL. 204-170

(51) INT. CL. B01D 13/00<sup>2</sup>

(19) (CA) **CANADIAN PATENT** (12)

(54) ULTRAFILTRATION AND ELECTRODIALYSIS METHOD AND  
APPARATUS

(72) Ahlgren, Richard M.,  
U.S.A.

(73) Granted to Coca-Cola Company (The)  
U.S.A.

(21) APPLICATION No. 284,689

(22) FILED 770815

No. OF CLAIMS 27

DISTRIBUTED BY THE PATENT OFFICE, OTTAWA  
CCA-274 (3-80)

**BEST AVAILABLE COPY**

284689

1088024

OCT 21 1980

ABSTRACT OF THE DISCLOSURE

A combination electrodialysis method and apparatus comprising ultrafiltration membrane cell pairs interposed between a cation-selective membrane and an ion-nonselective membrane. The solution to be treated is fed to one side of the ultrafiltration membrane cell, a concentrating solution is delivered between the cation-selective and ion-nonselective membranes, and an electric field is applied across the assembly. Cations pass through the ion-selective membranes, ions of both polarities and weakly ionized substances pass through the ultrafiltration membrane which rejects the larger sized particles and molecules and anions pass through the ion-selective membrane to maintain electrical balance.

1088024

BACKGROUND OF THE INVENTION

This invention relates to fluid separation and permeation.

One method of permeation separation involves electro-dialysis wherein the solution to be demineralized is fed into one or more cells defined by ion-selective membranes. When an electric field is applied across the separation cells, negative ions are drawn through anion-permeable membranes toward the cathode, while positive ions are drawn through cation-permeable membranes toward the anode whereby the feed solution is continually deionized.

One prior art type of separation apparatus employs filtration membranes in combination with electrodialysis cells for the removal of relatively large particles in addition to ionic particles. This type of apparatus is effective for separating the constituents of protein solutions such as cheese whey which contains proteins, lactose and minerals, commonly referred to as ash. The protein is separated by the filtration membranes while the anion and cation membranes separate the lactose from the ash which is typically potassium chloride. However, such protein solutions also typically include other anionic materials, such as weakly ionized amino acids, which tend to irreversibly foul anion membranes.

SUMMARY OF THE INVENTION

It is a general object of the present invention to provide a new and improved method and apparatus for separating the constituents of a protein solution.

A more specific object of the present invention is to provide a system for separating the constituents of a protein solution wherein fouling of the ion selective membranes is minimized.

How these and other objects and advantages of the



1088024

present invention are accomplished will become apparent from the detailed description thereof taken with the accompanying drawing. Generally, however, in a preferred form, the invention includes a permeation separation device comprising a plurality of cells defined by a filtration membrane flanked by pairs of cation selective and neutral or ion-nonselective membranes.

In one form, this invention comprises the combination of an enclosure, membrane support means disposed within the enclosure, a plurality of membranes supported in spaced  
10 relation by the membrane support means to form a plurality of permeation cells within the enclosure, and electrode means disposed in spaced relation relative to the sides of the membranes, for supplying an electric field thereacross. A first one of the membranes is selective to ions having one charge and a second one of the membranes is ion-nonselective for passing ions of either charge. A filtration member disposed between the first and second ones of the membranes defines at least one filtration cell therebetween with one side of the first one of the membranes and a permeate collecting cell  
20 with one side of the second one of the membranes. It also comprises means for delivering fluid under pressure to at least one filtration cell. In a further form of the invention, the first one of the membranes is cation selective and the ion-nonselective membrane passes both cations and anions. In still a further form of the invention, a fourth membrane which is ion-nonselective is disposed adjacent the other side of the first one of the membranes to define a first ion concentration cell and a fifth membrane which is selective to ions having one charge is disposed adjacent the other side of the second  
30 one of the membranes to define a second ion concentration cell.

## 1088024

In yet still a further form of the invention, the filtration membrane is selective of particles in the ultrafiltration range. In still another form of the invention, the membranes are arranged such that the ultrafiltration membrane is arranged between pairs of membranes with each membrane pair consisting of a cation selective membrane and an ion-nonselective membrane with a different membrane type of each pair being immediately adjacent the ultrafiltration membrane to define at least one ultrafiltration cell, permeate cell and two ion  
10 concentration cells. In yet still another form of the invention, the ultrafiltration cell includes an inlet and an outlet and including means for adjusting the fluid pressure within the ultrafiltration cell and means for recirculating at least a portion of the fluid leaving the outlet of the ultrafiltration cells to the inlet thereof. In a further form of the invention, it also includes means for selectively removing ultrafiltration concentrate from the recirculating means and for selectively introducing unconcentrated fluid to the ultrafiltration cell. The ultrafiltration membrane may  
20 comprise an anisotropic, microporous formal membrane which may be polyvinyl. Each of the cells may include fluid inlet and outlet means, and including means for circulating fluid into and out of each of the cells.

The filtration apparatus of this invention in one form comprises (a) a fluid enclosure including  $3N+1$  membranes supported in parallel spaced relation therein between opposite end walls thereof,  $N$  being a number between 1 and 10, the first, fourth and every third one thereafter of the membranes being selective to ions of a first charge, the second and  
30 every third one thereafter of the membranes being ion-

1088024

nonselective membranes, and the third and every third one thereafter of the membranes being ultrafiltration membranes whereby a plurality of cells are defined with the enclosure comprising: (i) ultrafiltration cells between adjacent ultrafiltration membranes and membranes selective to ions of a first charge, (ii) permeate cells between adjacent ultrafiltration membranes and ion-nonselective membranes, (iii) ion collection cells between adjacent ion selective and ion-nonselective membranes, and (iv) two cells defined by  
10 the end walls and the first membrane and last one of the ion-nonselective membranes; (b) electrode means in the last named cells for supplying an electric field across the remainder of the cells, and (c) means for introducing fluid to be concentrated and deionized into each ultrafiltration cell within the enclosure. The invention may further include circulating means for continuously introducing and removing fluid from the ultrafiltration cells, the circulating means including means for regulating the fluid pressure within the cells and means for selectively discharging fluid  
20 leaving the cells from the apparatus and introducing additional fluid to be deionized and concentrated to the ultrafiltration cells. The invention may further include means for independently circulating fluids through each of the permeate, ion collection and end cells.

Another form of the invention is a filtration process comprising the steps of: providing a filtration system including at least one ultrafiltration cell pair which is defined by an ultrafiltration membrane disposed between a pair of ion permeable membranes, a first one of which is  
30 cation selective and the other of which is at least cation and anion permeable, applying an electric field across the

1088024

cell pair, the cathode being arranged on the side of the housing the first ion-permeable membrane, and injecting a fluid to be simultaneously ultrafiltered and deionized under pressure into a first cell of the cell pair formed by the ultrafiltration membrane and one of the ion permeable membranes, whereby ionic constituents of the fluid are drawn out of the cell pair toward one direction relative to the field and whereby permeate is forced through the ultrafiltration membrane into the second cell of the cell pair. The

10 filtration system of the process may include a plurality of cell pairs and simultaneous injection of the fluid into a first one of the cells of each of the cell pairs. The ion-permeable membranes of the filtration system of the process may be substantially impermeable to the fluid injected into the first one of the cells of the cell pairs and fluid may be injected within the enclosure on the sides of the ion selective membranes opposite the ultrafiltration membranes. Concentrated fluid may be removed from the first one of the cells of the cell pair after ultrafiltration and deionization thereof, and

20 part of the removed fluid recirculated in the first cells. The process may further include the steps of removing a portion of the concentrated and deionized fluid from the filtration system and simultaneously adding fresh fluid to be ultrafiltered and deionized to maintain the liquid volume in the system substantially constant. The ultrafiltration membranes of the process may be anisotropic, microporous, polyvinyl formal membranes. The fluid injected into a first one of the cells of each of the cell pairs may be cheese whey.

A further form of the invention comprises, in

30 combination, a plurality of membranes, an enclosure including means for supporting the membranes in spaced relation within

1088024

the enclosure, electrode means in spaced relation on opposite sides of the membranes for providing an electric field thereacross, at least one of the membranes being selective to ions having one polarity and at least a second one of the membranes being ion-permeable and ion-nonselective, an ultrafiltration membrane disposed adjacent at least one of the ion selective membranes, and pressure means for delivering the fluid to be treated to the gap between at least two of the membranes. The combination may further include feed  
10 liquid circulating means coupled to the enclosure at spaced apart points between the membranes. The ultrafiltration member of the combination may be disposed between the ion selective membrane and an ion-nonselective membrane. The combination may also be characterized by a first group of the membranes being selective to ions having one polarity and a second group of the membranes being ion-nonselective and a third group of the membranes being ultrafiltration membranes, the membranes of the first and second groups of membranes being disposed in alternating spaced apart relation,  
20 the ultrafiltration membranes being disposed between at least some of the membranes of the first and second groups. The combination may be further characterized by the membranes being generally planar and disposed in a generally parallel relation. The combination may be still further characterized by one of the membranes of the first group being disposed adjacent one end of the enclosure and one of the membranes of the second group being disposed adjacent the other end of the enclosure, and the electrode means comprising a pair of electrodes, one of the electrodes being disposed adjacent  
30 each end of the enclosure.



1088024

BRIEF DESCRIPTION OF THE DRAWING

The single FIGURE is a schematic diagram of a permeation separation apparatus according to a preferred embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The single FIGURE of the drawing schematically illustrates the permeation separation apparatus 10 according to the present invention to include a cell pack 12, a feed solution injection, protein recirculation and removal system 14, a permeate recirculation and removal system 16, an ash recirculation and removal system 18, an anolyte rinse system 20 and a catholyte rinse system 21. It will be appreciated that the apparatus illustrated in the drawing is exemplary and modifications thereof can be made without departing from the scope of the present invention.

Cell pack 12 may be any well known type of membrane assembly such as a plate and frame assembly wherein a plurality of suitably perforated gaskets 22 support and seal the peripheries of a plurality of planar membranes 30, 31 and 32 in parallel spaced relation to form a series of parallel permeation cells 33a, 33b, 33c and end cells 36 and 37. Each permeation cell is defined by two of the membranes and the gaskets and the end cells 36 and 37 are respectively defined by membranes 31 and 32 and end caps 35. Disposed within end cell 36 is a suitable anode 38 and a cathode 40 is disposed in the opposite end cell 37. Anode 38 and cathode 40 are

1088024

connected respectively to the positive and negative terminals of a suitable power source (not shown) through leads 41 and 42. Enclosure 24 also includes suitable couplings (not shown) for admitting and removing liquids from each of cells 33a, 33b, 33c, 36 and 37. The components of the cell pack 12 are held in an abutting relation by suitable clamps or tie rods (not shown). In addition, the membranes 30 and 31 which define the cells 33c are suitably supported so that they can withstand the pressures commonly employed in filtration systems, e.g., on  
10 the order of 10-100 pounds psi or more.

Membranes 30 are filtration membranes, preferably in the ultrafiltration range; membranes 31 are cation-permeable, anion-impermeable membranes; and membranes 32 are neutral or cation and anion permeable membranes. With respect to the ion permeability of ultrafiltration membranes 30, it is essential that membranes 30 be permeable to either positive or negative ions and preferably they are neutral membranes which are permeable to ions of either charge. A wide variety of suitable materials are known to the ultrafiltration and  
20 electrodialysis arts which may be used in the present invention. The primary criteria for ultrafiltration membranes 30 are the ion permeability just described and pore size selectivity. For each particular application, a membrane is selected which will reject the large molecular weight constituents to be concentrated. The neutral membranes 32 may be of any suitable materials, such as cellophane and pass both anions and cations. However, anions tend to flow through membranes 32 in preference to cations as a result of the tendency for the liquid in cell 33a to remain ionically neutral. Membranes 31 and 32 are then  
30 selected after considering the water permeability, flow velocities, ionic rejection capabilities and the nature of the ionic constituents to be encountered in a particular job. All

## 1088024

of the membranes, of course, must possess sufficient tensile strength to withstand ultrafiltration operating pressures.

A preferred material for use for ultrafiltration membranes 30 are microporous and anisotropic polyvinyl formal membranes on fabric supports. Such membranes and their method of preparation are disclosed in United States Patent No. 3,988,245 issued October 26, 1976 to D.G.J. Wang and entitled "Anisotropic Polyvinyl Formal Resin Microporous Membrane and its Preparation", which United States patent is expressly incorporated by reference herein. Such membranes are especially preferred for use in the present invention because they are capable of withstanding normal operating pressures, and because they can withstand repeated contact with acidic and caustic cleaning solutions, the use of which will be described below.

Suitable materials for use as membranes 31 include cation exchange resins having active ion capture sites. Membranes 31 can be, for example, MC-3142 cation exchange membranes manufactured by Ionac Chemical Cybron Corporation, while membranes 32 can be, for example, reconstituted cellulose, which typically has electrical resistance in the range of 20-30 ohm-cm<sup>2</sup> for 0.5N NaCl and is ion-nonselective. Properties for a membrane 31 fabricated from MC-3142 are set forth in the following Table I.

TABLE I

<u>Property</u>	<u>MC-3142</u>
Electrical Resistance (ohm-cm <sup>2</sup> )	
0.1N NaCl	9.1
1.0N NaCl	3.4
% Permselectivity	
0.5N NaCl/1.0N NaCl	94.1
0.2N NaCl/0.1N NaCl	99.0

1088024

TABLE I (cont'd)

<u>Property</u>	<u>MC-3142</u>
Water Permeability	
ml/hr/ft <sup>2</sup> /30 psi ml/hr/ft <sup>2</sup> /10 psi	Negligible Negligible
Thickness	6 mils
Capacity	
meq/g <sup>2</sup> meq/cm <sup>2</sup>	1.06 0.021
Dimensional Stability	Good
10 Mullen Burst Strength (PSI)	185

In the illustrated embodiment, membranes 31 and 32 respectively form the membrane walls at end chambers 36 and 37, and proceeding from the left to the right of the FIGURE, the membrane arrangement is 31, 32, 30, 31, 32 ..... 32. Between end cells 36 and 37, and again proceeding from left to right in the FIGURE, are repetitive cell groups comprising an ash permeate cell 33a defined by membranes 31 and 32, a filtration permeation cell 33b defined by a membrane 30 and 32, and a filtration concentration cell 33c defined by membranes 30 and 31. The illustrated embodiment shows two such repetitive cell groups but any whole number multiple of cells may be employed ranging from 1 up to 50 or more. As an example, the membrane sheets may be 3.5 in. by 12 in. which provide an effective membrane area of 25 in.<sup>2</sup> per membrane when partially covered by gaskets 22.

Referring now to fluid transport systems 14, 16, 18, 20 and 21, the filtration product injection, recirculation and removal system 14 may include a pump 50 for circulating liquid to be concentrated and demineralized from a tank 51 to each of filtration concentration cells 33c through inlet manifold pipe 52, outlet manifold pipe 53, and return pipe 54. A suitable pressure regulator or valve 55 is connected into

## 1088024

manifold 53 for adjusting the pressure in ultrafiltration concentration cells 33a. In addition, a three way valve 56 is connected to manifold 53 for selectivity returning fluid exiting chamber 33a to tank 51 through pipe 54, for, alternatively, discharging the demineralized, concentrated product through pipe 58 or for partially performing both functions simultaneously. Tank 51 may also be connected by pipe 60 and valve 61 to a source of feed solution (not shown). It will be appreciated then when valve 56 is set to couple  
10 pipe manifold 53 to discharge pipe 58 and when valve 61 is set to couple pipe 60 to tank 51, the system is in a continuous mode. On the other hand, when valve 56 is set to couple pipe 53 to pipe 54 and valve 61 closed, the system is in a recirculation mode.

The permeate recirculation and removal system 16 is similar to system 14 and includes a circulating pump 70 for circulating permeate through permeate cells 33b through inlet manifold pipe 71 while permeate is removed from cells 33b by outlet manifold pipe 72. A three-way valve 73 may connect  
20 manifold pipe 72 to a holding tank 74 through pipe 75 or to permeate discharge through pipe 76. By a proper setting of valve 73, system 16 can be operated for discharge or recirculation.

Waste or ash recirculation and removal system 18 also includes a pump 80 for recirculating waste liquid to waste concentration cells 33a through inlet manifold pipe 81 while further concentrated waste is removed from these cells by outlet manifold pipes 82. A three-way valve 83 may connect manifold pipe 82 to holding tank 84 by pipe 85 and  
30 to waste pipe 86. Here again, the proper adjustment of valve 83 the system 18 can be set for discharge or recirculation.

The electrode rinse system 20 includes a pump 90,

## 1088024

connected by an inlet pipe 91 to one end of cell 36 and to a rinse solution holding tank 93, which in turn is connected by pipe 94 to the other end of cell 37. Rinse system 21 for cell 37 is identical and the same components are identified by the same reference numerals as in system 20 except that they are distinguished by a prime (').

The method of operation of permeation apparatus 10 can be advantageously described in connection with the demineralization and separation of proteins and lactose from cheese whey. For purposes of this description, it will be assumed that the ash content of whey is exclusively  $K+Cl^-$ , it being realized that actually other ionic constituents are present in cheese whey. An electric field is initially applied between electrodes 38 and 40. For example, for the seven cell group of the illustrated embodiment using 3.5 x 12" membranes, voltages may range between 30-40 volts, at 1.5-3.5 amps, but these values should not be taken as limiting as suitable operating parameters will vary widely depending on the resistance of the entire cell pack 12. Raw whey is then introduced through pipe 60 into ultrafiltration product injection, recirculation and removal system 14 which in turn feeds the raw material by pump 50 into cells 33c at a pressure of 10-100 psi or more. The desired pressure is set by adjustment of pressure regulator 56. In each of cells 33c, chloride ions, lactose and water are forced through filtration membranes 30 into cell 33b. Potassium ions pass through membranes 31 toward cathode 42 into cells 33a. The chloride ions pass through membranes 32 as a result of the tendency to create an ionic balance. As a result, both potassium and chloride ions collect in cells 33a whereby these ions may be removed through manifold 82. Protein is rejected by membranes 30 and is removed through manifold 53 and demineralized

## 1088024

permeate containing lactose is withdrawn through manifold 72.

By appropriate adjustment of valves 56, 61, 73 and 83, the system can be run continuously. At the initial stages of the process, it may be desired to recirculate protein concentrate until desired solids and mineral levels are reached. This is accomplished by setting valves 56 and 61 in the recirculation mode. After the desired levels are reached, the entire batch of protein concentrate may be discharged through pipe 58, or valve 56 may be opened slightly to bleed product from the system through pipe 58. If the latter method is selected, total liquid volumes can be maintained in system 14 by adjusting valve 61 to admit corresponding volumes of raw whey. The same procedures may be followed in systems 16 and 18, with demineralized permeate (lactose) and waste concentrate being removed as desired. It is preferred to rinse electrode cells 36 and 37 continuously by passing a dilute sulphuric acid solution through the cells using electrode rinse systems 20 and 21. Sodium sulphite may be substituted for the sulphuric acid and a number of additional electrode rinse compositions are known to the electrodialysis art.

It may also be desirable from time to time to thoroughly cleanse the membranes within cell pack 12 using membrane cleaning procedures known to the art. In one such procedure, the entire cell pack is rinsed with water, rinsed with a caustic cleaning solution, rinsed with water, rinsed with an acidic cleaning solution and again rinsed thoroughly with water at intervals which will depend on the types of feed solutions and products encountered. Because cheese whey provides such an excellent base for bacterial growth, it may be necessary to clean apparatus 10 daily when the system is being used for cheese whey separation. The cleaning solution may be introduced through system 14 or otherwise. Another

cleaning procedure which is especially valuable for the ultra-filtration membrane cell pair comprises reversing the direction of flow periodically through cells 33 to remove accumulations of proteins at the surfaces of ultrafiltration membrane 30.

Table I shows that the water permeability of membranes 31 and 32 is negligible, and for this reason circulating solutions should be pumped through system 18 to carry ash from cells 33a. Again, suitable solutions can be chosen from those known to the electrodialysis art, one  
10 example being a 0.5 to 1.0% sodium chloride solution in distilled water. It is not necessary to employ additional fluids in system 16 as the ultrafiltration membrane is highly water permeable under operating pressures.

While the illustrated embodiment has been described in connection with the demineralization and concentration of cheese whey proteins, the inventive concept is equally applicable to other systems. Paper processing plants produce large volumes of waste mixtures including lignin, sugars and acid. Such plants may employ the process to concentrate  
20 and de-acidity lignin in cells 33c, to separate and de-acidify sugars in cells 33b and to concentrate the acidic components in cells 33a. Proper selection of membranes, operating voltages and injection pressures may readily be made after the components of the system are analyzed with respect to their molecular weights, ionic characteristics, etc. Also, while the foregoing description has discussed the use of cation and neutral ion-selective membranes, it is also contemplated that anion and neutral ion-selective membranes could be employed in combination with filtration membranes in an analogous manner.

30 While the invention has been described in connection with a particular preferred embodiment, the invention can be variously embodied and is to be limited solely by the claims which follow.



1088024

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. The combination of:

an enclosure,

membrane support means disposed within said enclosure,  
a plurality of membranes supported in spaced relation by said  
membrane support means to form a plurality of permeation  
cells within said enclosure,

electrode means disposed in spaced relation relative  
to the sides of said membranes, for supplying an electric  
field thereacross,

a first one of said membranes being selective  
to ions having one charge and a second one of said membranes  
being ion-nonselective for passing ions of either charge, and

a filtration membrane disposed between said first and  
second ones of said membranes to define at least one  
filtration cell therebetween with one side of said first  
one of said membranes and a permeate collecting cell with  
one side of the second one of said membranes,

means for delivering fluid under pressure to at  
least one filtration cell.

2. The invention set forth in claim 1 wherein the  
first one of said membranes is cation selective and said ion-  
nonselective membrane passes both cations and anions.

3. The combination set forth in claim 2 wherein a  
fourth membrane which is ion-nonselective is disposed adjacent  
the other side of said first one of said membranes to define  
a first ion concentration cell and a fifth membrane which is  
selective to ions having said one charge is disposed adjacent  
the other side of the second one of said membranes to define  
a second ion concentration cell.

4. The combination set forth in claim 3 wherein said

filtration membrane is selective of particles in the ultrafiltration range.

5. The combination set forth in claim 4 wherein said membranes are arranged such that said ultrafiltration membrane is arranged between pairs of membranes with each membrane pair consisting of a cation selective membrane and an ion-non-selective membrane with a different membrane type of each pair being immediately adjacent said ultrafiltration membrane to define at least one ultrafiltration cell, a permeate cell and two ion concentration cells.

6. The invention set forth in claim 5 wherein said ultrafiltration cell includes an inlet and an outlet and including means, for adjusting the fluid pressure within said ultrafiltration cell and means for recirculating at least a portion of the fluid leaving the outlet of said ultrafiltration cells to the inlet thereof.

7. The invention set forth in claim 6 further including means for selectively removing ultrafiltration concentrate from said recirculating means and for selectively introducing unconcentrated fluid to said ultrafiltration cell.

8. The invention set forth in claim 7 wherein said ultrafiltration membrane comprises an anisotropic, microporous formal membrane.

9. The invention set forth in claim 7 wherein each of said cells includes fluid inlet and outlet means, and including means for circulating fluid into and out of each of said cells.

10. The invention set forth in claim 8 wherein said ultrafiltration membranes comprise an anisotropic, microporous, polyvinyl formal membrane.

11. A filtration apparatus comprising:

(a) a fluid enclosure including  $3N+1$  membranes

1088024

supported in parallel spaced relation therein between opposite end walls thereof, N being a number between 1 and 10, the first, fourth and every third one thereafter of said membranes being selective to ions of a first charge, the second and every third one thereafter of said membranes being ion-nonselective membranes, and the third and every third one thereafter of said membranes being ultrafiltration membranes whereby a plurality of cells are defined within said enclosure comprising:

(i) ultrafiltration cells between adjacent ultrafiltration membranes and membranes selective to ions of a first charge,

(ii) permeate cells between adjacent ultrafiltration membranes and ion-nonselective membranes,

(iii) ion collection cells between adjacent ion selective and ion-nonselective membranes, and

(iv) two cells defined by said end walls and the first membrane and last one of said ion-non-selective membranes;

(b) electrode means in said last named cells for supplying an electric field across the remainder of said cells, and

(c) means for introducing fluid to be concentrated and deionized into each ultrafiltration cell within said enclosure.

12. The invention set forth in claim 11 further including circulating means for continuously introducing and removing fluid from said ultrafiltration cells, said circulating means including means for regulating the fluid pressure within said cells and means for selectively discharging fluid leaving said cells from said apparatus and introducing additional fluid to be deionized and concentrated to said ultrafiltration cells.

**1088024**

13. The invention set forth in claim 12 including means for independently circulating fluids through each of said permeate, ion collection and end cells.

14. The invention set forth in claim 13 wherein said ultrafiltration membranes are anisotropic, microporous, polyvinyl formal membranes.

15. A filtration process comprising:

providing a filtration system including at least one ultrafiltration cell pair which is defined by an ultrafiltration membrane disposed between a pair of ion permeable membranes, a first one of which is cation selective and the other of which is at least cation and anion permeable,

applying an electric field across said cell pair, the cathode being arranged on the side of said housing said first ion-permeable membrane, and

injecting a fluid to be simultaneously ultrafiltered and deionized under pressure into a first cell of said cell pair formed by said ultrafiltration membrane and one of said ion permeable membranes, whereby ionic constituents of said fluid are drawn out of said cell pair toward one direction relative to said field and whereby permeate is forced through said ultrafiltration membrane into the second cell of said cell pair.

16. The invention set forth in claim 15 wherein said filtration system includes a plurality of cell pairs and wherein said fluid is simultaneously injected into a first one of the cells of each of said cell pairs.

17. The invention set forth in claim 16 wherein said ion-permeable membranes are substantially impermeable to the fluid injected into said first one of said cells of said cell pairs and injecting fluid within said enclosure on the sides of said ion selective membranes opposite said ultrafiltration membranes.

**1088024**

18. The invention set forth in claim 17 and removing concentrated fluid from said first one of said cells of said cell pair after ultrafiltration and deionization thereof and recirculating at least a part of said removed fluid back into said first cells.

19. The invention set forth in claim 18 further including the steps of removing a portion of the concentrated and deionized fluid from the filtration system and simultaneously adding fresh fluid to be ultrafiltered and deionized to maintain the liquid volume in the system substantially constant.

20. The invention set forth in claim 16 wherein said ultrafiltration membranes include anisotropic, microporous, polyvinyl formal membranes.

21. The invention set forth in claim 16 wherein said fluid is cheese whey.

22. The combination of:

a plurality of membranes,

an enclosure including means for supporting said membranes in spaced relation within said enclosure,

electrode means in spaced relation on opposite sides of said membranes for providing an electric field there-across,

at least one of said membranes being selective to ions having one polarity and at least a second one of said membranes being ion-permeable and ion-nonselective,

an ultrafiltration membrane disposed adjacent at least one of said ion selective membranes,

and pressure means for delivering the fluid to be treated to the gap between at least two of said membranes.

23. The combination set forth in claim 22 and including feed liquid circulating means coupled to said enclosure at spaced apart points between said membranes.

## 1088024


24. The combination set forth in claim 22 wherein said ultrafiltration membrane is disposed between said ion selective membrane and an ion-nonselective membrane.

25. The combination set forth in claim 22 wherein a first group of said membranes are selective to ions having one polarity and a second group of said membranes are ion-nonselective and a third group of said membranes are ultrafiltration membranes, the membranes of said first and second groups of membranes being disposed in alternating spaced apart relation, the ultrafiltration membranes being disposed between at least some of the membranes of said first and second groups.

26. The combination set forth in claim 25 wherein said membranes are generally planar and disposed in a generally parallel relation.

27. The combination set forth in claim 26 wherein one of the membranes of said first group is disposed adjacent one end of said enclosure and one of the membranes of said second group being disposed adjacent the other end of said enclosure, and means comprising a pair of electrodes, one of said electrodes being disposed adjacent each end of said enclosure.





**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**